

Inox A2

62 430


DIN 7504 M - (similar ISO 15481)

VIS AUTOPERCEUSES TETE CYLINDRIQUE POZIDRIVE

POZIDRIVE PAN HEAD SELF DRILLING SCREWS

BOHRSCHRAUBEN MIT LINSKOPF UND KREUZSCHLITZ Z

TORNILLOS AUTOTALADRANTES CABEZA CILINDRICA POZIDRIVE



d	3,5 (6)	3,9 (7)	4,2 (8)	4,8 (10)
d2	6,9	7,5	8,2	9,5
k	2,6	2,8	3,05	3,55
+	2	2	2	2
Capacité de perçage	2	2	3	4

d x L	Code	Cond.	kg/100	d x L	Code	Cond.	kg/100
3,5X9,5	624303,5X9,5	200	0,104	4,2X25	624304,2X25	200	0,257
3,5X13	624303,5X13	200	0,119	4,2X32	624304,2X32	200	0,306
3,5X16	624303,5X16	200	0,132	4,2X38	624304,2X38	200	0,339
3,5X19	624303,5X19	200	0,144	4,8X13	624304,8X13	200	0,285
3,5X25	624303,5X25	200	0,170	4,8X16	624304,8X16	200	0,310
3,9X13	624303,9X13	200	0,136	4,8X19	624304,8X19	200	0,335
3,9X16	624303,9X16	200	0,160	4,8X22	624304,8X22	200	0,359
3,9X19	624303,9X19	200	0,178	4,8X25	624304,8X25	200	0,384
3,9X22	624303,9X22	200	0,200	4,8X32	624304,8X32	200	0,391
3,9X25	624303,9X25	200	0,208	4,8X38	624304,8X38	200	0,491
3,9X32	624303,9X32	200	0,235	4,8X45	624304,8X45	200	0,548
4,2X13	624304,2X13	200	0,183	4,8X50	624304,8X50	200	0,589
4,2X16	624304,2X16	200	0,170	4,8X60	624304,8X60	200	0,671
4,2X19	624304,2X19	200	0,190	4,8X70	624304,8X70	200	0,754



Perce seulement l'aluminium / Drills only aluminium

Informations d'utilisation voir page 43 / Using instructions : see page 43