



SIX LOBES RAISED COUNTERSUNK HEAD DECKING SCREWS WITH TWIN THREAD REFERENCES 62324 (AISI 410) AND 64324 (S.S. A4)

▶ FEATURES

Martensitic stainless steel C1 graded (62324)

Austenitic stainless steel A4 graded (64324)

Lubrican coating, WAX type

Thin raised countersunk head (angle 60°)

Ribs under head

Spiral thread - double thread

Anti-splitting point, cutting point type (angle 23-27°)

Conformity with DTU 51.4.



Hard wood patios: exotic wood, leafy wood (A4 only)

Wood outside floor for frame

Inappropriate for salt and/or chlorine environments

▶ INSTALLATION RULES

35 to 40 screws/m²


Screws installed at minimum 2 cm beside the slat

Essential pre-drilling

▶ DIMENSIONS (mm)

d	4	4,5	5
dk	6,0	7,0	7,7
k	3,8	4,3	4,5
TX	15	20	25







▶ RANGE

AISI 410

d x L	Product code	Packaging	Over-packaging	Weight kg/100
4X40	623244X40	200	3600	0,220
4X50	623244X50	200	1600	0,250
4,5X50	623244,5X50	200	1600	0,340
4,5X60	623244,5X60	200	1600	0,410
5X50	623245X50	200	1600	0,420
5X60	623245X60	200	1600	0,575
5X70	623245X70	100	800	0,600
5X80	623245X80	100	800	0,650

STAINLESS STEEL A4

d x L	Product code	Packaging	Over-packaging	Weight kg/100
4X40	643244X40	200	1600	0,220
4,5X50	643244,5X50	200	1600	0,340
5X50	643245X50	200	1600	0,420
5X50	643245X50BRUN	200	1600	0,420
5X50	643245X50SEAU	500	2500	0,420
5X60	643245X60	200	1600	0,510
5X60	643245X60BRUN	200	1600	0,510
5X60	643245X60SEAU	500	2500	0,510
5X70	643245X70	100	800	0,600
5X80	643245X80	100	800	0,660

▶ BUCKETS

