

Acton

SIX LOBES SMALL COUNTERSUNK HEAD DECKING SCREWS REFERENCE 62326 (S.S. A2)

▶ FEATURES

Austenitic stainless steel A2 graded (62326)

Lubrican coating - WAX type

Small countersunk headTête fraisée étroite (angle 60-65°)

Ribs under head

Anti-splitting point - cutting point type (angle 22-28°)

Notched threading (2 cuts for \emptyset 4; 3 cuts for \emptyset 4,5 and \emptyset 5)



Patio in hard wood: exotic wood, leafy wood

Wood outside floor for frame

▶ INSTALLATION RULES

35 to 40 screws/m²


Screws installed at 2 cm minimum besides the slat

Essential pre-drilling

▶ DIMENSIONS (mm)

d	4	4,5	5
dk	6,2	7,0	7,7
k	3,4	3,7	3,9
TX	15	20	25







▶ RANGE

STAINLESS STEEL A2

d x L	Product code	Packaging	Over-packaging	Weight kg/100
4X40	623264X40	200	1600	0,220
4,5X50	623264,5X50	200	1600	0,660
4,5X60	623264,5X60	200	1600	0,410
4,5X70	623264,5X70	200	1600	0,443
5X40	623265X40	200	1600	0,410
5X50	623265X50	200	1600	0,420
5X50	623265X50BRUN	200	1600	0,420
5X50	623265X50SEAU	500	2500	0,420
5X60	623265X60	200	1600	0,510
5X60	623265X60BRUN	200	1600	0,510
5X60	623265X60SEAU	500	2500	0,510
5X70	623265X70	100	800	0,600
5X80	623265X80	100	800	0,660
5X100	623265X100	100	800	0,822

BUCKETS

